BMW Media Information

12/2010

Valid from 3/2011

Specifications. The new BMW 6 Series Convertible.

640i, 650i



	E	BMW 640i Convertible	BMW 650i Convertible
D1			
Body		0.14	0.14
No. of doors/seats		2/4	2/4
Length/width/height	mm	4894 / 1894 / 1365	4894 / 1894 / 1365
Wheelbase	mm	2855	2855
Track, front/rear	mm	1600 / 1657	1600 / 1657
Ground clearance	mm	123	123
Turning circle	m	11.7	11.7
Tank capacity	ca. l	70	70
Cooling system incl heating		9.3	11.4
Engine oil ¹⁾		6.5	8.5
Weight, unladen, to DIN/EU	kg	1840 / 1915	1940 / 2015
Max load to DIN	kg	450	450
Max permissible weight	kg	2290	2390
Max axle load, front/rear	kg	1100 / 1290	1180 / 1310
Max trailer load, braked (12%)/unbraked	kg	-/-	-1-
Max roof load/towbar	kg	-/-	-1-
Luggage comp capacity	- 1	300-350	300-350
Air drag	c _X x A	0.31 x 2.23	0.32 x 2.23
Engine			
Configuration/No of		Straight / 6 / 4	V90/8/4
Engine technology		BMW TwinPower Turbo,	BMW TwinPower Turbo,
		direct injection,	direct injection
	f	fully variable valve control	
		(VALVETRONIC)	
Effective capacity	CC	2979	4395
Bore/stroke	mm	89.6 / 84.0	88.3 / 89.0
Compression ratio	:1	10.2	10.0
Fuel grade		min RON 91	min RON 91
Output	kW/hp	235 / 320	300 / 407
at	rpm	5800-6000	5500-6400
Torque	Nm	450	600
at	rpm	1300-4500	1750-4500
Electrical system			
Battery/Installation	Ah/–	90/luggage comp	105/luggage comp
Alternator	A/W	210 / 2940	210 / 2940
Driving dynamics and saf	ety		
Suspension, front	Double track control arm with separate lower track arm level, aluminium, small steering roll radius, anti-dive		
Suspension, rear	Integral-V multi-arm axle, aluminium, with steering function, anti-squat and anti-dive, double acoustic separation		
Brakes, front		Single-piston alumi	nium swing-calliper disc brakes in frame structure
Diameter	mm	348 x 30 / vented	374 x 36 / vented
Brakes, rear		Single-pist	ton aluminium swing-calliper disc brakes
Diameter	mm	345 x 24 / vented	345 x 24 / vented
Driving stability systems		Standard: DSC incl	ABS, ASC and DTC (Dynamic Traction Control),
3 , ,			trol), DBC (Dynamic Brake Control), Dry Braking function, tion, Start-Off Assistant; optional: Adaptive Drive
Safety equipment	Standard: airbags for driver and front passenger, side airbags with combined head airbags for driver and front passenger, three-point inertia-reel seatbelts on all seats with belt latch tensioner and belt force limiter integrated in the front seats, crash-activated head restraints at the front, roll-over protection system, crash sensors, Tyre Defect Indicator		
Steering			Power Steering (EPS) with Servotronic; ptional: Integral Active Steering
Steering ratio, overall	:1	17.1	17.1
Tyres, front/rear		225/55 R17 97Y RSC	245/45 R18 96Y RSC
Rims, front/rear		8J x 17 LM	8J x 18 LM

BMW Media Information

12/2010

Valid from 3/2011

Specifications. The new BMW 6 Series Convertible. 640i, 650i

		I	BMW 640i Convertible	BMW 650i Convertible	
BMW Conne	ctedDrive				
Comfort	otcubillo	Optional: BMW Assist incl Enquiry Service, remote-control functions and V-Info+ (Traffic Info plus), BMW TeleServices, integration of mobile devices			
Infotainment		Optional: internet access, BMW Online incl Park Info, National Info, Google Local Search, News, Realtime Weather, BMW Routes, Office functions, Bluetooth Audio Streaming and Online Update Music Tracks			
Safety		r	Optional: Adaptive Headlights with corne adaptive headlight range control, High I ear-view camera, Surround View incl Top \ pedestrian recognition, Head-Up Display, Lane Departure Warning, Speed Limit In	Beam Assistant, Park Distance Control, /iew and Side View, BMW Night Vision with Parking Assistant, Lane Change Warning,	
Transmissio	n				
Type of gearb	OX		Eight-speed automa	atic with Steptronic	
Gear ratios		:1	4.714	4.714	
		:1	3.143	3.143	
	III	:1	2.106	2.106	
	IV	:1	1.667	1.667	
	V	:1	1.285	1.285	
	VI	:1	1.000	1.000	
	VII	:1	0.839	0.839	
	VIII	:1	0.667	0.667	
	R	:1	3,295	3.317	
Final drive		:1	3.232	3.077	
Performance	• •				
Power-to-weig	ght ratio	kg/kW	7.8	6.5	
Output per litr	e	kW/l	78.9	68.3	
Acceleration	0–100	S	5.7	5.0	
	0–1000	S	25.2	23.8	
in 4th gear	80-120	S	_	-	
Top speed		km/h	250	250	
BMW					
BMW EfficientDynamics standard features			Brake Energy Regeneration with recuperation display, Auto Start-Stop function (BMW 640i), intelligent lightweight construction, on-demand operation of ancillary units, air flap control (BMW 640i), Electric Power Steering (EPS), detachable a/c compressor, tyres with reduced rolling resistance		
Fuel consum	ntion El'				
Urban	ipuon EU	l/100km	10.9	15.5	
Extra-urban		1/100km	6.2	7.9	
Combined		1/100km	7.9	10.7	
CO ₂		g/km	185	249	
Emission ratin	α.	y/kill	EU5		
LITISSION TAUN	9		בטט	EUS	

Specifications apply to ACEA markets; data relevant to homologation applicable in part only to Germany (weight)

¹⁾ Oil change